

ENSTRÜMAN ARA BAĞLANTI KABLOSU
INSTRUMENT PATCH CABLES

KULLANIM ALANLARI

Bütün ses sistemlerinde, çok çeşitli tipte konnektörleri olan ara bağlantı kablolarına ihtiyaç vardır. Sistemlerin kendilerine özgü gereksinimleri göz önünde tutularak bir grup adaptör kablosunun yedekte bulundurulması sistem içerisinde doğabilecek sorunlara anında müdahale imkanı sağlar. Bu kabloların, küçük çaplı ve hafif olmasının öncelikle tercih edildiği stüdyo ortamlarında iletkenlerin ayrı ayrı ekranlanmasıyla da dış elektrik kaynaklarının etkisi önlenmiştir. Bireysel olarak ekranlanmış bu kablolar kullanım amaçlarına göre ayrı profillerde üretilmektedir.

APPLICATION

One of the most essential requirements of all audio systems are patch cables and adapters, presenting a wide variety of connectors. In case of realising the self-characteristical necessity of the system, it would be advisable to keep a group of adapters in reserve, in order to remove arising problems instantly. As result of their small construction and lightness, these cables would be hold in estimation especially in studio atmospheres, just the same reason give the individual sheathed conductors, which turn away external electrical source effects. The individual sheathed cables are produced in various profiles according to their application.

ELEKTİRİKSEL ÖZELLİKLER/ELECTRICAL CHARACTERISTICS

SEMBOL SYMBOL	İLETKEN DİRENCİ CONDUCTOR RESISTANCE	EKRAN DİRENCİ SHIELD RESISTANCE	KAPASİTE (İLETKEN/EKRAN) CAPACITANCE (COND/SCREEN)
EK.102	< 223 Ohm / km	< 65 Ohm / km	290 pF / mt.
EK.103	< 138 Ohm / km	< 55 Ohm / km	290 pF / mt.
EK.104	< 85 Ohm / km	< 41 Ohm / km	92 pF / mt.
EK.D102	< 223 Ohm / km	< 65 Ohm / km	290 pF / mt.
EK.D103	< 85 Ohm / km	< 55 Ohm / km	140 pF / mt.
EK.D104	< 85 Ohm / km	< 62 Ohm / km	170 pF / mt.
EK.D105	< 82 Ohm / km	< 26 Ohm / km	62 pF / mt.

MEKANİK ÖZELLİKLER

Min. Bükme Yarıçapı	Sabit Tesis	5 x Dış Çap
	Hareketli Tesis	10 x Dış Çap
Çalışma Sıcaklığı	Sabit	-25°C +70°C
	Hareketli	-5°C..... 70°C

MECHANICAL CHARACTERISTICS

Min. Bending Radius	Fixed Installation	5 x Overall Diameter
	Mobile Use	10 x Overall Diameter
Temperature Range	Static	-25°C +70°C
	Flexing	-5°C..... 70°C

SEMBOL SYMBOL	ÜRÜN KODU CODE NO.	KESİT CROSS SECTION	DIŞ ÇAP OVERALL DIAMETER	STANDART AMBALAJ STANDARD LENGTH
EK.102	21112102	0.09mm ²	Ø2.0mm	100 m.
EK.103	21112103	0.15mm ²	Ø3.2mm	100 m.
EK.104	21336104	0.22mm ²	Ø4,5mm	100 m.
EK.D102	21212102	0.09mm ²	2.0x4,1mm	100 m.
EK.D103	21222103	0.22mm ²	3.2x6.5mm	100 m.
EK.D104	21222104	0.22mm ²	3.5x6.5mm	100 m.
EK.D105	21232105	0.22mm ²	4.7x9.0mm	100 m.